







Pallet scale

2815

- ► Approvable, class III
- ▶ Portability due to transport handle and rollers
- ▶ Low scale weight of approx. 40 kg
- ▶ 6 m measurement cable to connect pallet scale and terminal
- ▶ Can be combined with all approvable Soehnle Professional terminals



Features

- Approvable, class III
- Portability due to transport handle and rollers
- Low scale weight of approx. 40 kg
- Stainless steel configuration: Weighing platform made from 1.4301 stainless steel, load cell made from stainless steel, protection class IP 68
- Painted configuration: Painted configuration: painted, load cell: nickel-plated steel, protection class: IP 67
- Terminal box protection class IP 65 (protection class can be increased to IP 68 with potted terminal box, see accessories)
- ▶ 6 m measurement cable to connect pallet scale and terminal
- Dimensions: 1,190 x 840 x 80 mm (leg width: 120 mm)
- Load capacity: 3,000 kg
- ▶ Can be combined with all approvable Soehnle Professional terminals



Products

Order number Variation	Approvable	Division g	Maximum load kg	Model
2815.11.900 Pallet scale	Yes	100 200	300 600	Painted
2815.12.900 Pallet scale	Yes	200 500	600 1.500	Painted
2815.13.900 Pallet scale	Yes	500 1.000	1.500 3.000	Painted
2815.21.900 Pallet scale	Yes	100 200	300 600	Stainless steel
2815.22.900 Pallet scale	Yes	200 500	600 1.500	Stainless steel



Accessories

Order number Variation		Description
2510.06.001		Weighing platform made of 1.4301 stainless steel load capacity: 300 kg
2503.06.001		Widening kit, stainless steel, kit consists of 2 installed parts, width of each L profile: 100 mm
2510.05.001		Weighing platform made from painted steel, load capacity 300 kg
2510.11.001		Transport device with stand for terminal, painted
2516.01.005		Terminal box in protection class IP 68, potted
2540.01.006	⟨Ex⟩	ATEX zone 2/22 configuration for weighing platforms 2815.11.900, 2815.12.900, 2815.13.900
2540.01.005	⟨Ex⟩	ATEX zone 2/22 configuration for weighing platforms 2815.21.900, 2815.22.900
2503.06.002		Widening kit, painted, kit consists of 2 installed parts, width of each L profile: 100 mm